



# Moisture Balance

## CONTACT US

Phone: 310-830-6601

FAX: 310-830-9336

Email: info@sepor.com  
& services@sepor.com

## LOCATIONS

### WEST COAST

718 N. Fries Avenue  
Wilmington, CA 90744

### EAST COAST

3740 NW 124th Ave  
Coral Springs, FL 33065



## Description:

The PMB's fast response time and easy-to-use functionality make it the ideal moisture analyzer for a range of different applications. The automatic test setting function lets you quickly run multiple tests without additional user input and the built-in memories lets you store that data for future reference. The PMB offers smart features that have been developed to give

you the ultimate performance for moisture analysis.

## Features:

- Built-in memory for storing products and settings
- 3 settings for heating sample include fast ramp up, step and standard
- Automatic test start setting for when the lid is closed
- Date and time
- Full range tare
- Zero Tracking
- Quick and easy to configure through the keypad
- Multilingual display
- Large backlit display with dual text prompts
- Capacity tracker
- Non-slip adjustable leveling feet
- Color coded, sealed keypad
- Large stainless steel pan
- Lock down mounting slot for Kensington™ type lock and cable
- Overload protection
- Splash proof to protect from accidental spills
- Spirit Level
- Single Halogen Lamp 400W
- RS-232 and USB interface
- Calibration facilities for temperature and weight
- Mains Power Cord
- Pan lifter to easily remove samples

Catalog Number	Model No.	Capacity	Readability	Pan Size
<b>130D-120</b>	PMB 53	50g	0.001g /0.01%	3.9" Ø / 100mm Ø
130D-125	PMB 202	200g	0.01g /0.05%	3.9" Ø / 100mm Ø