



## PRODUCT BULLETIN

SEPOR, INC.  
718 N. FRIES AVE.  
P. O. BOX 578  
WILMINGTON, CA 90748  
PHONE: 310-830-6601  
FAX: 310-830-9336

# 2' X 3' Vibrating Screen

The universal 24" (W) X 36" (L) vibrating screen is a versatile production screen that is a short stroke, high frequency screen, which is ideal for sizing particle sizes below 1/4". It works well with small quantities of larger size particles as well. It is available in one deck, two deck models, with open style or enclosed style options. Materials of construction are high carbon steel and stainless steel. A 1/4 HP/1725 RPM/115 V/1 Ph/60 Hz TEFC motor is standard. 220 V/1 Ph/50 Hz is available. The screen deck is shipped completely assembled and ready to operate.

### Mounting options for screen use:

The Vibrating Screen may be suspended by cables furnished by the customer.

The Vibrating Screen may be mounted on a fixed base furnished by the customer.

The Vibrating Screen may be mounted on a **pitch-adjustable mobile stand**, which can be furnished by Sepor. This mobile stand ideal for determining the proper angle of inclination for screening various materials, and it gives the screen mobility.



### Open Style 2' X 3' Single Deck Screen With Mobile Pitch-Adjustable Stand

Screen Panels are available in stainless steel for the Vibrating Screen in sizes ranging from 1" openings down to 200 mesh.

For further information concerning this screen, or a particular screening application, contact SEPOR.

**In the United States and Canada,  
Our Toll-Free Telephone Number is  
800-753-6463**