



SEPOR, INC.  
718 N. FRIES AVE.  
P. O. BOX 578  
WILMINGTON, CA 90748  
PHONE: 310-830-6601  
FAX: 310-830-9336

## 8" BATCH PRESSURE FILTER

The batch 3 gallon, 8 inch diameter pressure filter is designed for batch filtration of lab scale quantities of slurries under pressures of 60 PSI. The filter is tested at 80 PSI, but normal operating pressure is up to 60 PSI. The filter is available in carbon steel construction or 316 stainless steel construction. It features a 8" diameter by 14" height removable cylinder, a 10" square base plate with threaded bottom and side discharge ports, a swing away lid for easy filling, emptying, and is shipped completely assembled. Also included are 1/4" NPT quick connect air coupling for air supply, one standard polypropylene filter cloth with nominal 25 micron pore opening, one hi-seal filter cloth with built in rubber gasket, one package of 100 high wet strength filter papers (25 micron pore opening), pressure gauge, petcock valve for charging/discharging air, safety relief valve.



CATALOG NUMBER	DESCRIPTION	Ship Weight (lbs)
070B-010	8" Pressure Filter, Carbon Steel	120
070B-020	8" Pressure Filter, 316 SS	120
070B-011	Extra Polypropylene Filter Cloth	0.5
070B-012	Extra Pkg of 100 Filter Papers	1
070B-018	Extra Hi-Seal Filter Cloth	0.5