



PRODUCT BULLETIN

SEPOR, INC.
718 N. FRIES AVE.
P. O. BOX 578
WILMINGTON, CA 90748
PHONE: 310-830-6601
FAX: 310-830-9336

Web Site: <http://www.sepor.com>

VARIABLE SPEED STIRRERS

The heavy duty stirrers with digital read-out can handle high volume/high viscosity stirring. Ideal for batches up to 30 gallons depending on viscosity. These stirrers feature brushless direct current motors, there no sparks. Has a unique two speed transmission that transfers power to the chuck with 95% efficiency. Transmission electronically shifts between high torque and high speed range. Soft touch controls allow repeatable speed adjustments. Digital display of RPM or Torque. Maintains set speed as solution viscosity changes. Rugged metal housing and hollow drive shaft. All units come complete with a high-quality adjustable chuck with 3/8" capacity and 1/2" by 5" mounting rod. Ideal for continuous use. Motors are 110V, 50/60HZ, with transformer for 220 V/1 Ph/50 Hz input. Rated at 1/5 HP. Automatic overload protection. Not explosion-proof.



Mixer Model DC3030 has a speed range from 30 to 3,000 RPM, with 30 inch-pounds (480 in-oz) of torque at 600 rpm.

Stainless Steel Support Stand Made of stainless steel. It consists of a heavy base which can accommodate vessels up to 18" diameter. Support rod is 5/8" by 28" high on SS110, and 48" high on SS111, up to three support rods can be mounted on each base.

PP152 PROPELLER WITH SHAFT, three-bladed, 2" diameter prop on a 1/4" x 10" long shaft. Blades can be twisted for desired pitch

Clamp Holder For attaching clamps, electric stirrers, air powered stirrers, extension rings, etc. to support stands. For rods up to 3/4" diameter. Aluminum alloy. Weight limit is 8 lbs. (12 lbs. For CH632J).

Transformer has on/off switch, inlet cord with plug for 220 V/1 Ph/50 Hz and outlet receptacle for 110 V/1 Ph/50 Hz.