

SEPOR, INC.
718 N Fries Ave.
Wilmington, CA 90744
310 830 6601
Fax: 310 830 9336
<http://www.sepor.com>



Assay Grade Litharge

Sepor furnishes assay grade litharge in 25 Kg (55 Lbs.) UN conforming metal pails, in a free flowing granular form, with 95% -25 mesh. Assay grade litharge is primarily used in fire assaying. Fire assaying is the quantitative determination of precious metals in a ore. Assay Grade litharge is the purest form of litharge, conforming to the specifications below.

It is furnished FOB Wilmington, California, although it is generally not stored at our location in California, but can be shipped there in a couple of days.

Litharge, Assay Grade ANALYSIS RESULTS

Compound	Required Cond. (Min or Max)	Percent Detected
Lead Monoxide	99% Min	99.59%
SiO ₂	0.1% Max	0.01%
CaO	0.05% Max	0.02%
Al ₂ O ₃	0.04% Max	0.01%
Fe	0.025% Max	0.02%
Zn	0.0005% Max	0.0001%
Insoluable Matter	0.3% Max	0.05%
As	0.0005% Max	0.00%
Bismuth	0.0004% Max	0.00%
Metals	0.5% Max	
Silver	0.005 OzT/Ton Max	0.004 Oz/T
Gold	1 PPB Max	< 1 PPB
Size	95% pass 20 Mesh	95% - 20 Mesh